



california **water** technologies LLC

8851 Dice Road Santa Fe Springs, CA 90670
(866) 337-7427

Liquid Ferric Chloride Drinking Water Grade

Description

California Water Technologies Liquid Ferric Chloride is a concentrated solution of Iron III Chloride (FeCl_3) in water. It is manufactured from high purity raw materials.

Principal Uses

Potable water treatment

- Turbidity reduction
- Color elimination
- Enhanced coagulation, NOM and DBP precursor removal
- Softening solids sedimentation
- Membrane pre-treatment
- Sludge reduction
- Filter conditioning
- Arsenic Removal

Wastewater treatment

- Phosphate precipitation and removal
- Enhanced sedimentation
- Dewatering of all types of sludge streams
- Polymer flocculant enhancement
- Sulfide based odor elimination
- Struvite control

Appearance:	A dark red/brown liquid Specifications
Concentrations:	
FeCl_3	39% - 44%
FeCl_2	0.75% maximum
Free Acid as HCl	1.0% maximum Drinking Water Grade
Insolubles	0.008% (80 ppm) maximum
Radionuclides	None
Specific gravity:	1.40 – 1.47
Viscosity:	12.1 centipoises for a 40% solution
Crystallization:	39% FeCl_3 (4°F); 44% FeCl_3 (45°F)
ANSI/NSF Standard 60 Certified:	Maximum use level – 250 ppm as solution
CAS No.:	7705-08-0
UN Classification:	UN2582, Ferric Chloride Solution SQC data available on request

Document Number.:	Page 1 of 2	Revision No.:	Revision Date:
		3	1/18/2011

Shipping containers:

55 gallon drums
Tank Trucks

Manufacturing Location

Santa Fe Springs, California

Handling & Safety

Ferric Chloride is considered to be hazardous by definition of the Hazard Communication Standard (29 CFR 1910.1200) and should be handled in a manner that is consistent with acceptable practices. Please obtain the Ferric Chloride Material Safety Data Sheet for complete up-to-date information.

Under normal situations the only protective equipment required in the use of Liquid Ferric Chloride are splash proof chemical goggles and rubber gloves. Liquid Ferric Chloride will stain both clothing and skin and it is recommended that, to protect against this occurrence, other protective clothing be worn as is appropriate.

Ferric Chloride reacts strongly with many metals. However, most handling situations are reliably addressed through the use of common compatible plastic materials such as FRP, PVC, Polyethylene, Polypropylene and Teflon. For additional information consult your equipment supplier.

For additional information and to place orders call: 866-337-7427

California Water Technologies
Serving The Water and Wastewater Industry

This bulletin and the information contained herein are offered solely for your consideration, investigation and verification. NO REPRESENTATIONS OR WARRANTIES, EXPRESS OR IMPLIED, OF MERCHANTABILITY OR OTHERWISE, ARE MADE OR CONTAINED HEREIN. California Water Technologies' exclusive responsibility for any claims, including claims based on negligence, arising in connection with the information contained herein or the subsequent purchase, use, storage or handling of the product will in no event exceed California Water Technologies' sale price for the product with respect to which damages are claimed. In no event will California Water Technologies be liable for any incidental or consequential damages arising in connection with the information contained herein or the subsequent purchase, use, storage or handling of the product. User accepts full responsibility for compliance with all applicable Federal, state and local laws and regulations. Nothing contained herein will be construed to constitute permission or a recommendation to use the product in any process or formulation covered by a patent a patent application owned by California Water Technologies or by others.

Document Number.:	Page 2 of 2	Revision No.:	Revision Date:
		3	1/18/2011